## HOUSE SUBSTITUTE FOR SENATE BILL NO. 120

A bill to amend 1949 PA 300, entitled "Michigan vehicle code,"

by amending section 719 (MCL 257.719), as amended by 2017 PA 35.

## THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

- 1 Sec. 719. (1) A vehicle unloaded or with load shall not exceed
- 2 a height of 13 feet 6 inches. The owner of a vehicle that collides
- 3 with a lawfully established bridge or viaduct is liable for all
- 4 damage and injury resulting from a collision caused by the height
- 5 of the vehicle, whether the clearance of the bridge or viaduct is
- 6 posted or not.
- 7 (2) Lengths described in this subsection shall be known as the
- 8 normal length maximum. Except as provided in subsection (3), the
- 9 following vehicles and combinations of vehicles shall not be
- 10 operated on a highway in this state in excess of these lengths:

- 1 (a) Subject to subsection (9), any single vehicle: 40 feet; a
- 2 crib vehicle on which logs are loaded lengthwise of the vehicle:
- 3 42.5 feet; any single bus or motor home: 45 feet.
- 4 (b) Articulated buses: 65 feet.
- 5 (c) Notwithstanding any other provision of this section, a
- 6 combination of a truck and semitrailer or trailer, or a truck
- 7 tractor, semitrailer, and trailer, or truck tractor and semitrailer
- 8 or trailer, designed and used exclusively to transport assembled
- 9 motor vehicles or bodies, recreational vehicles, or boats: 65 feet.
- 10 A combination of a truck and semitrailer or trailer, or a truck
- 11 tractor, semitrailer, and trailer, or a truck tractor and
- 12 semitrailer or trailer designed and used to transport boats from
- 13 the manufacturer: , or a stinger-steered combination: 75 feet. A
- 14 STINGER-STEERED COMBINATION: 80 FEET. The load on the combinations
- 15 of vehicles described in this subdivision may extend an additional
- 16 3 feet beyond the front and 4 feet beyond the rear of the
- 17 combinations of vehicles, EXCEPT THAT THE LOAD ON A STINGER-STEERED
- 18 COMBINATION MAY EXTEND AN ADDITIONAL 4 FEET BEYOND THE FRONT AND 6
- 19 FEET BEYOND THE REAR. Retractable extensions used to support and
- 20 secure the load that do not extend beyond the allowable overhang
- 21 for the front and rear shall not be included in determining length
- 22 of a loaded vehicle or vehicle combination.
- 23 (d) Truck tractor and semitrailer combinations: no overall
- 24 length, the semitrailer: 50 feet.
- 25 (e) Except as provided in subdivision (j), truck and
- 26 semitrailer or trailer: 59 feet.
- 27 (f) Except as provided in subdivision—SUBDIVISIONS (g) AND

- 1 (K), truck tractor, semitrailer, and trailer, or truck tractor and
- 2 2 semitrailers: 59 feet.
- 3 (g) A truck tractor, semitrailer, and trailer, or a truck
- 4 tractor and 2 semitrailers, in which no semitrailer or trailer is
- 5 more than 28-1/2 feet long: 65 feet. This subdivision only applies
- 6 while the vehicle is being used for a business purpose reasonably
- 7 related to picking up or delivering a load and only if each
- 8 semitrailer or trailer is equipped with a device or system capable
- 9 of mechanically dumping construction materials or dumping
- 10 construction materials by force of gravity.
- (h) More than 1 motor vehicle, wholly or partially assembled,
- 12 in combination, utilizing 1 tow bar or 3 saddle mounts with full
- 13 mount mechanisms and utilizing the motive power of 1 of the
- 14 vehicles in combination: 55 feet.
- 15 (i) A recreational vehicle that has its own motive power, in
- 16 combination with a trailer: 65 feet or, if the operator of the
- 17 recreational vehicle has a group commercial motor vehicle
- 18 designation on his or her operator's or chauffeur's license, 75
- **19** feet.
- 20 (j) Truck and trailer combinations designed and used to
- 21 transport agricultural drainage tubing: 75 feet.
- 22 (K) A TOWAWAY TRAILER TRANSPORTER COMBINATION: 82 FEET. AS
- 23 USED IN THIS SUBDIVISION, "TOWAWAY TRAILER TRANSPORTATION
- 24 COMBINATION" MEANS THAT TERM AS DEFINED IN 49 USC 31111.
- 25 (3) Notwithstanding subsection (2), the following vehicles and
- 26 combinations of vehicles shall not be operated on a designated
- 27 highway of this state in excess of these lengths:

- 1 (a) Truck tractor and semitrailer combinations: no overall
- 2 length limit, the semitrailer 53 feet. All semitrailers longer than
- 3 50 feet shall have a wheelbase of 37.5 to 40.5 feet plus or minus
- 4 0.5 feet, measured from the kingpin coupling to the center of the
- 5 rear axle or the center of the rear axle assembly. City, village,
- 6 or county authorities may prohibit stops of vehicles with a
- 7 semitrailer longer than 50 feet within their jurisdiction unless
- 8 the stop occurs along appropriately designated routes, or is
- 9 necessary for emergency purposes or to reach shippers, receivers,
- 10 warehouses, and terminals along designated routes.
- 11 (b) Truck EXCEPT AS PROVIDED IN SUBSECTION (2) (K), TRUCK and
- 12 semitrailer or trailer combinations: 65 feet, except that a person
- 13 may operate a truck and semitrailer or trailer designed and used to
- 14 transport saw logs, pulpwood, and tree length poles that does not
- 15 exceed an overall length of 70 feet or a crib vehicle and
- 16 semitrailer or trailer designed and used to transport saw logs that
- 17 does not exceed an overall length of 75 feet. A crib vehicle and
- 18 semitrailer or trailer designed to and used to transport saw logs
- 19 shall not exceed a gross vehicle weight of 164,000 pounds. A person
- 20 may operate a truck tractor and semitrailer designed and used to
- 21 transport saw logs, pulpwood, and tree length wooden poles with a
- 22 load overhang to the rear of the semitrailer which does not exceed
- 23 6 feet if the semitrailer does not exceed 50 feet in length.
- (c) Notwithstanding subsection (5)(d), a truck tractor with a
- 25 log slasher unit and a log saw unit: no overall limit if the length
- 26 of each unit does not exceed 28-1/2 feet, or the overall length of
- 27 the log slasher unit and the log saw unit, as measured from the

- 1 front of the first towed unit to the rear of the second towed unit
- 2 while the units are coupled together, does not exceed 58 feet. The
- 3 coupling devices of the truck tractor and units set forth in this
- 4 subdivision shall meet the requirements established under the motor
- 5 carrier safety act of 1963, 1963 PA 181, MCL 480.11 to 480.25.
- 6 (d) Truck EXCEPT AS PROVIDED IN SUBSECTION (2) (K), TRUCK
- 7 tractor and 2 semitrailers, or truck tractor, semitrailer, and
- 8 trailer combinations: no overall length limit, if the length of
- 9 each semitrailer or trailer does not exceed 28-1/2 feet each, or
- 10 the overall length of the semitrailer and trailer, or 2
- 11 semitrailers as measured from the front of the first towed unit to
- 12 the rear of the second towed unit while the units are coupled
- 13 together does not exceed 58 feet.
- 14 (e) More than 1 motor vehicle, wholly or partially assembled,
- in combination, utilizing 1 tow bar or 3 saddle mounts with full
- 16 mount mechanisms and utilizing the motive power of 1 of the
- 17 vehicles in combination: 97 feet.
- 18 (f) Truck tractor and lowboy semitrailer combinations: no
- 19 maximum overall length, if the lowboy semitrailer does not exceed
- 20 59 feet, except as otherwise permitted under this subdivision. A
- 21 lowboy semitrailer wheelbase shall not exceed 55 feet as measured
- 22 from the kingpin coupling to the center of the rear axle. A lowboy
- 23 semitrailer more than 59 feet in length shall not operate with more
- 24 than any combination of 4 axles on the lowboy unless an oversized
- 25 load permit is issued by the state transportation department or a
- 26 local authority with respect to highways under its jurisdiction. As
- 27 used in this subdivision, "lowboy semitrailer" means a flatbed

- 1 semitrailer with a depressed section that has the specific purpose
- 2 of being lowered and raised for loading and unloading.
- 3 (4) Notwithstanding any other provision of this section, a
- 4 combination of a truck and semitrailer, or truck tractor and
- 5 semitrailer, used exclusively to transport assembled motor vehicles
- 6 or bodies that have a trailer length of 53 feet may have a load
- 7 that extends an additional 3 feet beyond the front of the trailer
- 8 and 4 feet beyond the rear of the trailer. Retractable extensions
- 9 used to support and secure the load that do not extend beyond the
- 10 allowable overhang for the front and rear shall not be included in
- 11 determining length of a loaded vehicle or vehicle combination. The
- 12 total overall length loaded of the combination of vehicles
- 13 described in this subsection shall not exceed 79 feet.
- 14 (5) The following combinations and movements are prohibited:
- 15 (a) A truck shall not haul more than 1 trailer or semitrailer,
- 16 and a truck tractor shall not haul more than 2 semitrailers or 1
- 17 semitrailer and 1 trailer in combination at any 1 time, except that
- 18 a farm tractor may haul 2 wagons or trailers, or garbage and refuse
- 19 haulers may, during daylight hours, haul up to 4 trailers for
- 20 garbage and refuse collection purposes, not exceeding in any
- 21 combination a total length of 55 feet and at a speed limit not to
- 22 exceed 15 miles per hour.
- 23 (b) A combination of vehicles or a vehicle shall not have more
- 24 than 11 axles, except when operating under a valid permit issued by
- 25 the state transportation department or a local authority with
- 26 respect to a highway under its jurisdiction.
- 27 (c) Any combination of vehicles not specifically authorized

- 1 under this section is prohibited.
- 2 (d) Except as provided in subsection (3)(c), a combination of
- 3 2 semitrailers pulled by a truck tractor, unless each semitrailer
- 4 uses a fifth wheel connecting assembly that conforms to the
- 5 requirements of the motor carrier safety act of 1963, 1963 PA 181,
- 6 MCL 480.11 to 480.25.
- 7 (e) A-EXCEPT AS PROVIDED IN SUBSECTION (2) (C), A vehicle or a
- 8 combination of vehicles shall not carry a load extending more than
- 9 3 feet beyond the front of the lead vehicle.
- (f) A vehicle described in subsections (2) (e) and (3) (e)
- 11 employing triple saddle mounts unless all wheels that are in
- 12 contact with the roadway have operating brakes.
- 13 (6) All combinations of vehicles under this section shall
- 14 employ connecting assemblies and lighting devices that are in
- 15 compliance with the motor carrier safety act of 1963, 1963 PA 181,
- **16** MCL 480.11 to 480.25.
- 17 (7) The total gross weight of a truck tractor, semitrailer,
- 18 and trailer combination or a truck tractor and 2 semitrailers
- 19 combination that exceeds 59 feet in length shall not exceed a ratio
- 20 of 400 pounds per engine net horsepower delivered to clutch or its
- 21 equivalent specified in the handbook published by the Society of
- 22 Automotive Engineers, Inc. (SAE), 1977 edition.
- 23 (8) A person who violates this section is responsible for a
- 24 civil infraction. The owner of the vehicle may be charged with a
- 25 violation of this section.
- 26 (9) The provisions in subsections (2)(a) and (3)(b)
- 27 prescribing the length of a crib vehicle on which logs are loaded

- 1 lengthwise do not apply unless 23 USC 127(d) is amended to allow
- 2 crib vehicles carrying logs to be loaded as described in this
- 3 section.
- 4 (10) As used in this section:
- 5 (a) "Designated highway" means a highway approved by the state
- 6 transportation department or a local authority with respect to a
- 7 highway under its jurisdiction.
- 8 (b) "Length" means the total length of a vehicle, or
- 9 combination of vehicles, including any load the vehicle is
- 10 carrying. Length does not include devices described in 23 CFR
- 11 658.16 and 23 CFR part 658, appendix D, 23 CFR 658.16 and 23 CFR
- 12 part 658, appendix D, as on file with the secretary of state are
- 13 adopted by reference. A safety or energy conservation device shall
- 14 be excluded from a determination of length only if it is not
- 15 designed or used for the carrying of cargo, freight, or equipment.
- 16 Semitrailers and trailers shall be measured from the front vertical
- 17 plane of the foremost transverse load supporting structure to the
- 18 rearmost transverse load supporting structure. Vehicle components
- 19 not excluded by law shall be included in the measurement of the
- 20 length, height, and width of the vehicle.
- 21 (c) "Stinger-steered combinations" "STINGER-STEERED
- 22 COMBINATION" means a truck tractor and semitrailer combination in
- 23 which the fifth wheel is located on a drop frame located behind and
- 24 below the rearmost axle of the power unit.
- 25 Enacting section 1. This amendatory act takes effect 90 days
- 26 after the date it is enacted into law.