

**SUBSTITUTE FOR
SENATE BILL NO. 120**

A bill to amend 1949 PA 300, entitled
"Michigan vehicle code,"
by amending section 719 (MCL 257.719), as amended by 2015 PA 208.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

1 Sec. 719. (1) A vehicle unloaded or with load shall not exceed
2 a height of 13 feet 6 inches. The owner of a vehicle that collides
3 with a lawfully established bridge or viaduct is liable for all
4 damage and injury resulting from a collision caused by the height
5 of the vehicle, whether the clearance of the bridge or viaduct is
6 posted or not.

7 (2) Lengths described in this subsection shall be known as the
8 normal length maximum. Except as provided in subsection (3), the
9 following vehicles and combinations of vehicles shall not be
10 operated on a highway in this state in excess of these lengths:

11 (a) Subject to subsection (9), any single vehicle: 40 feet; a

1 crib vehicle on which logs are loaded lengthwise of the vehicle:
2 42.5 feet; any single bus or motor home: 45 feet.

3 (b) Articulated buses: 65 feet.

4 (c) Notwithstanding any other provision of this section, a
5 combination of a truck and semitrailer or trailer, or a truck
6 tractor, semitrailer, and trailer, or truck tractor and semitrailer
7 or trailer, designed and used exclusively to transport assembled
8 motor vehicles or bodies, recreational vehicles, or boats: 65 feet.

9 A combination of a truck and semitrailer or trailer, or a truck
10 tractor, semitrailer, and trailer, or a truck tractor and
11 semitrailer or trailer designed and used to transport boats from
12 the manufacturer: ~~or a stinger-steered combination:~~ 75 feet. **A**
13 **STINGER-STEERED COMBINATION: 80 FEET.** The load on the combinations
14 of vehicles described in this subdivision may extend an additional
15 3 feet beyond the front and 4 feet beyond the rear of the
16 combinations of vehicles, **EXCEPT THAT THE LOAD ON A STINGER-STEERED**
17 **COMBINATION MAY EXTEND AN ADDITIONAL 4 FEET BEYOND THE FRONT AND 6**
18 **FEET BEYOND THE REAR.** Retractable extensions used to support and
19 secure the load that do not extend beyond the allowable overhang
20 for the front and rear shall not be included in determining length
21 of a loaded vehicle or vehicle combination.

22 (d) Truck tractor and semitrailer combinations: no overall
23 length, the semitrailer: 50 feet.

24 (e) Truck and semitrailer or trailer: 59 feet.

25 (f) Except as provided in ~~subdivision~~ **SUBDIVISIONS** (g) **AND**
26 **(J)**, truck tractor, semitrailer, and trailer, or truck tractor and
27 2 semitrailers: 59 feet.

1 (g) A truck tractor, semitrailer, and trailer, or a truck
2 tractor and 2 semitrailers, in which no semitrailer or trailer is
3 more than 28-1/2 feet long: 65 feet. This subdivision only applies
4 while the vehicle is being used for a business purpose reasonably
5 related to picking up or delivering a load and only if each
6 semitrailer or trailer is equipped with a device or system capable
7 of mechanically dumping construction materials or dumping
8 construction materials by force of gravity.

9 (h) More than 1 motor vehicle, wholly or partially assembled,
10 in combination, utilizing 1 tow bar or 3 saddle mounts with full
11 mount mechanisms and utilizing the motive power of 1 of the
12 vehicles in combination: 55 feet.

13 (i) A recreational vehicle that has its own motive power, in
14 combination with a trailer: 65 feet or, if the operator of the
15 recreational vehicle has a group commercial motor vehicle
16 designation on his or her operator's or chauffeur's license, 75
17 feet.

18 **(J) A TOWAWAY TRAILER TRANSPORTER COMBINATION: 82 FEET. AS**
19 **USED IN THIS SUBDIVISION, "TOWAWAY TRAILER TRANSPORTATION**
20 **COMBINATION" MEANS THAT TERM AS DEFINED IN 49 USC 31111.**

21 (3) Notwithstanding subsection (2), the following vehicles and
22 combinations of vehicles shall not be operated on a designated
23 highway of this state in excess of these lengths:

24 (a) Truck tractor and semitrailer combinations: no overall
25 length limit, the semitrailer 53 feet. All semitrailers longer than
26 50 feet shall have a wheelbase of 37.5 to 40.5 feet plus or minus
27 0.5 feet, measured from the kingpin coupling to the center of the

1 rear axle or the center of the rear axle assembly. City, village,
2 or county authorities may prohibit stops of vehicles with a
3 semitrailer longer than 50 feet within their jurisdiction unless
4 the stop occurs along appropriately designated routes, or is
5 necessary for emergency purposes or to reach shippers, receivers,
6 warehouses, and terminals along designated routes.

7 (b) ~~Truck~~ **EXCEPT AS PROVIDED IN SUBSECTION (2) (J), TRUCK** and
8 semitrailer or trailer combinations: 65 feet, except that a person
9 may operate a truck and semitrailer or trailer designed and used to
10 transport saw logs, pulpwood, and tree length poles that does not
11 exceed an overall length of 70 feet or a crib vehicle and
12 semitrailer or trailer designed and used to transport saw logs that
13 does not exceed an overall length of 75 feet. A crib vehicle and
14 semitrailer or trailer designed to and used to transport saw logs
15 shall not exceed a gross vehicle weight of 164,000 pounds. A person
16 may operate a truck tractor and semitrailer designed and used to
17 transport saw logs, pulpwood, and tree length wooden poles with a
18 load overhang to the rear of the semitrailer which does not exceed
19 6 feet if the semitrailer does not exceed 50 feet in length.

20 (c) Notwithstanding subsection (5) (d), a truck tractor with a
21 log slasher unit and a log saw unit: no overall limit if the length
22 of each unit does not exceed 28-1/2 feet, or the overall length of
23 the log slasher unit and the log saw unit, as measured from the
24 front of the first towed unit to the rear of the second towed unit
25 while the units are coupled together, does not exceed 58 feet. The
26 coupling devices of the truck tractor and units set forth in this
27 subdivision shall meet the requirements established under the motor

1 carrier safety act of 1963, 1963 PA 181, MCL 480.11 to 480.25.

2 (d) ~~Truck~~ **EXCEPT AS PROVIDED IN SUBSECTION (2) (J), TRUCK**
3 tractor and 2 semitrailers, or truck tractor, semitrailer, and
4 trailer combinations: no overall length limit, if the length of
5 each semitrailer or trailer does not exceed 28-1/2 feet each, or
6 the overall length of the semitrailer and trailer, or 2
7 semitrailers as measured from the front of the first towed unit to
8 the rear of the second towed unit while the units are coupled
9 together does not exceed 58 feet.

10 (e) More than 1 motor vehicle, wholly or partially assembled,
11 in combination, utilizing 1 tow bar or 3 saddle mounts with full
12 mount mechanisms and utilizing the motive power of 1 of the
13 vehicles in combination: 97 feet.

14 (f) Truck tractor and lowboy semitrailer combinations: no
15 maximum overall length, if the lowboy semitrailer does not exceed
16 59 feet, except as otherwise permitted under this subdivision. A
17 lowboy semitrailer wheelbase shall not exceed 55 feet as measured
18 from the kingpin coupling to the center of the rear axle. A lowboy
19 semitrailer more than 59 feet in length shall not operate with more
20 than any combination of 4 axles on the lowboy unless an oversized
21 load permit is issued by the state transportation department or a
22 local authority with respect to highways under its jurisdiction. As
23 used in this subdivision, "lowboy semitrailer" means a flatbed
24 semitrailer with a depressed section that has the specific purpose
25 of being lowered and raised for loading and unloading.

26 (4) Notwithstanding any other provision of this section, a
27 combination of a truck and semitrailer, or truck tractor and

1 semitrailer, used exclusively to transport assembled motor vehicles
2 or bodies that have a trailer length of 53 feet may have a load
3 that extends an additional 3 feet beyond the front of the trailer
4 and 4 feet beyond the rear of the trailer. Retractable extensions
5 used to support and secure the load that do not extend beyond the
6 allowable overhang for the front and rear shall not be included in
7 determining length of a loaded vehicle or vehicle combination. The
8 total overall length loaded of the combination of vehicles
9 described in this subsection shall not exceed 79 feet.

10 (5) The following combinations and movements are prohibited:

11 (a) A truck shall not haul more than 1 trailer or semitrailer,
12 and a truck tractor shall not haul more than 2 semitrailers or 1
13 semitrailer and 1 trailer in combination at any 1 time, except that
14 a farm tractor may haul 2 wagons or trailers, or garbage and refuse
15 haulers may, during daylight hours, haul up to 4 trailers for
16 garbage and refuse collection purposes, not exceeding in any
17 combination a total length of 55 feet and at a speed limit not to
18 exceed 15 miles per hour.

19 (b) A combination of vehicles or a vehicle shall not have more
20 than 11 axles, except when operating under a valid permit issued by
21 the state transportation department or a local authority with
22 respect to a highway under its jurisdiction.

23 (c) Any combination of vehicles not specifically authorized
24 under this section is prohibited.

25 (d) Except as provided in subsection (3)(c), a combination of
26 2 semitrailers pulled by a truck tractor, unless each semitrailer
27 uses a fifth wheel connecting assembly that conforms to the

1 requirements of the motor carrier safety act of 1963, 1963 PA 181,
2 MCL 480.11 to 480.25.

3 (e) ~~A~~**EXCEPT AS PROVIDED IN SUBSECTION (2)(C),** A vehicle or a
4 combination of vehicles shall not carry a load extending more than
5 3 feet beyond the front of the lead vehicle.

6 (f) A vehicle described in subsections (2)(e) and (3)(e)
7 employing triple saddle mounts unless all wheels that are in
8 contact with the roadway have operating brakes.

9 (6) All combinations of vehicles under this section shall
10 employ connecting assemblies and lighting devices that are in
11 compliance with the motor carrier safety act of 1963, 1963 PA 181,
12 MCL 480.11 to 480.25.

13 (7) The total gross weight of a truck tractor, semitrailer,
14 and trailer combination or a truck tractor and 2 semitrailers
15 combination that exceeds 59 feet in length shall not exceed a ratio
16 of 400 pounds per engine net horsepower delivered to clutch or its
17 equivalent specified in the handbook published by the Society of
18 Automotive Engineers, Inc. (SAE), 1977 edition.

19 (8) A person who violates this section is responsible for a
20 civil infraction. The owner of the vehicle may be charged with a
21 violation of this section.

22 (9) The provisions in subsections (2)(a) and (3)(b)
23 prescribing the length of a crib vehicle on which logs are loaded
24 lengthwise do not apply unless 23 USC 127(d) is amended to allow
25 crib vehicles carrying logs to be loaded as described in this
26 section.

27 (10) As used in this section:

1 (a) "Designated highway" means a highway approved by the state
2 transportation department or a local authority with respect to a
3 highway under its jurisdiction.

4 (b) "Length" means the total length of a vehicle, or
5 combination of vehicles, including any load the vehicle is
6 carrying. Length does not include devices described in 23 CFR
7 658.16 and 23 CFR part 658, appendix d, 23 CFR 658.16 and 23 CFR
8 part 658, appendix d, as on file with the secretary of state are
9 adopted by reference. A safety or energy conservation device shall
10 be excluded from a determination of length only if it is not
11 designed or used for the carrying of cargo, freight, or equipment.
12 Semitrailers and trailers shall be measured from the front vertical
13 plane of the foremost transverse load supporting structure to the
14 rearmost transverse load supporting structure. Vehicle components
15 not excluded by law shall be included in the measurement of the
16 length, height, and width of the vehicle.

17 (c) ~~"Stinger-steered combinations"~~ **"STINGER-STEERED**
18 **COMBINATION"** means a truck tractor and semitrailer combination in
19 which the fifth wheel is located on a drop frame located behind and
20 below the rearmost axle of the power unit.

21 Enacting section 1. This amendatory act takes effect 90 days
22 after the date it is enacted into law.