HOUSE BILL No. 5000

June 26, 1991, Introduced by Rep. Gagliardi and referred to the Committee on Transportation.

A bill to amend section 719 of Act No. 300 of the Public Acts of 1949, entitled as amended

"Michigan vehicle code,"

as amended by Act No. 78 of the Public Acts of 1990, being section 257.719 of the Michigan Compiled Laws.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

- 1 Section 1. Section 719 of Act No. 300 of the Public Acts of
- 2 1949, as amended by Act No. 78 of the Public Acts of 1990, being
- 3 section 257.719 of the Michigan Compiled Laws, is amended to read
- 4 as follows:
- 5 Sec. 719. (1) Except as provided in subsection (2), a vehi-
- 6 cle unloaded or with load shall not exceed a height of 13 feet 6
- 7 inches. The owner of a vehicle which collides with a lawfully
- 8 established bridge or viaduct shall be liable for all damage and
- 9 injury resulting from a collision caused by the height of the

03489'91 TJS

- 1 vehicle, whether the clearance of the bridge or viaduct is posted
 2 or not.
- 3 (2) A truck, truck tractor, semitrailer, or trailer manufac-
- 4 tured on or after July 27, 1978, shall not be used to transport
- 5 flammable liquids, in bulk, having a flash point at or below 70
- 6 degrees Fahrenheit, if the truck, truck tractor, semitrailer, or
- 7 trailer exceeds 11 feet 8-1/2 inches in height. However, safety
- 8 equipment and those appurtenances which are required by state
- 9 law, when added to a vehicle, may cause the vehicle height to
- 10 exceed 11 feet 8-1/2 inches, but shall not cause the vehicle
- 11 height to exceed 13 feet 6 inches. A person who violates this
- 12 subsection is guilty of a misdemeanor.
- 13 (3) A vehicle, except a truck tractor, trailer, or semi-
- 14 trailer, including load, or articulated buses operated by a local
- 15 public transit system funded by Act No. 51 of the Public Acts of
- 16 1951, being sections 247.651 to 247.675 of the Michigan Compiled
- 17 Laws, shall not exceed a total length of 40 feet. The total
- 18 length of a semitrailer operating in a truck tractor and semi-
- 19 trailer combination shall not exceed 53 feet, including load.
- 20 All semitrailers longer than 50 feet shall have a wheelbase of
- 21 40.5 feet plus or minus 0.5 feet, measured from the kingpin cou-
- 22 pling to the center of the rear axles or to the center of the
- 23 tandem axle assembly if equipped with 2 axles. Articulated buses
- 24 operated by a local public transit system funded by Act No. 51 of
- 25 the Public Acts of 1951 may operate with a maximum length of 65
- 26 feet. A combination of truck tractor, semitrailer, and trailer,
- 27 or truck and semitrailer or trailer, or a combination of truck

1 tractor and 2 semitrailers, including load, shall not exceed a 2 total overall length of 59 feet except as provided for on routes 3 designated and approved by the state transportation department 4 and by local authorities with respect to highways under their 5 jurisdiction on which a person may operate a combination of a 6 truck tractor, semitrailer, and trailer or a truck tractor and 2 7 semitrailers with no limit on the overall combination length, if 8 the length of each semitrailer or trailer including load does not 9 exceed 28-1/2 feet or the overall length of the semitrailer and 10 trailer or 2 semitrailers as measured from the front of the first 11 towed unit to the rear of the second towed unit while the units 12 are coupled together does not exceed an overall length of 58 13 feet, including load. The state transportation department and 14 local authorities with respect to highways under their jurisdic-15 tion may designate highways where the overall length of a truck 16 and trailer or semitrailer shall not exceed 65 feet. A truck 17 tractor and semitrailer combination with a semitrailer length 18 longer than 50 feet shall not be allowed to operate with more 19 than 2 axles on the semitrailer. All truck tractor and semi-20 trailer combinations with a semitrailer length longer than 21 50 feet shall travel exclusively on highways designated by the 22 appropriate road authority. City, village, or county authorities 23 shall have the option of prohibiting stops within their jurisdic-24 tions unless the stop occurs along appropriately designated 25 routes, or is necessary for emergency purposes or to reach ship-26 pers, receivers, warehouses, and terminals along designated 27 routes. A truck tractor shall not haul more than 1 trailer and 1

- 1 semitrailer or more than 2 semitrailers in combination at any 1 2 time, except that a farm tractor may haul 2 wagons or trailers, A 3 TRUCK TRACTOR MAY HAUL NOT MORE THAN 4 SEMITRAILERS TO TRANSPORT 4 PASSENGERS ON A TRAIN OPERATED SOLELY FOR SIGHTSEEING PURPOSES, 5 or garbage and refuse haulers may, during daylight hours, haul up 6 to 4 trailers for garbage and refuse collection purposes, not 7 exceeding in any combination a total length of 55 feet at a speed 8 of not to exceed 15 miles per hour. In determining the length of 9 a vehicle or a vehicle combination under this subsection, the 10 length shall not be considered to include safety and energy con-11 servation devices including, but not be limited to, impact 12 absorbing bumpers, rear view mirrors, turn signals lamps, marker 13 lamos, steps and hand holds for entry and egress, flexible fender 14 extensions, mud flaps, or splash and spray suppressant devices; 15 load induced tire bulge; refrigeration or heating units; or air 16 compressors. A device shall be excluded from a determination of 17 length only if it is not designed or used for the carrying of 18 cargo. Semitrailers and trailers shall be measured from the 19 front vertical plane of the foremost transverse load supporting 20 structure to the rearmost transverse load supporting structure. 21 (4) If a combination of 2 semitrailers is pulled by a truck 22 tractor, a fifth wheel connecting assembly which conforms with 23 motor carrier safety rules promulgated by the department of state
- 24 police pursuant to the motor carrier safety act of 1963, Act
 25 No. 181 of the Public Acts of 1963, as amended, being sections
 26 480.11 to 480.21 of the Michigan Compiled Laws, shall be used on
 27 each semitrailer.

- 1 (5) A train of vehicles or a vehicle operated alone shall 2 not carry a load extending more than 3 feet beyond the front of 3 the train of vehicles or vehicle.
- 4 (6) A motor vehicle, trailer, or semitrailer whose frame or
- 5 body extends more than 36 inches beyond the rear of its rear axle
- 6 and is more than 30 inches above the roadway shall not be oper-
- 7 ated on the highways of this state unless equipped with a fender
- 8 or bumper on the extreme rear of the frame or body. The bumper
- 9 shall extend downward from the rear of the frame or body to
- 10 within 30 inches of the roadway and be of substantial
- 11 construction. In addition to the requirements of subsection (7),
- 12 -no A vehicle which is required by federal law to have an under-
- 13 ride guard of not more than 22 inches above the roadway shall NOT
- 14 be operated upon the highways of this state without such an
- 15 underride quard.
- 16 (7) A truck tractor and semitrailer combination with a semi-
- 17 trailer length longer than 50 feet whose frame or body extends
- 18 more than 36 inches beyond the rear of its rear axle and is more
- 19 than 30 inches above the roadway shall not be operated on the
- 20 highways of this state unless equipped with an underride guard on
- 21 the extreme rear of the frame or body. The underride guard shall
- 22 meet all of the following requirements:
- 23 (a) Provide a continuous horizontal beam having a maximum
- 24 ground clearance of 22 inches, as measured with the vehicle empty
- 25 and on level ground.
- (b) Extend to within 4 inches of the lateral extremities of
- 27 the trailer on both left and right sides.

- 1 (8) A truck tractor and semitrailer combination with a
- 2 semitrailer length longer than 50 feet shall not be operated on
- 3 the highways of this state at the times specified in section 684
- 4 unless equipped with all of the following lamps and reflectors,
- 5 in addition to any other lamps and reflectors required under this
 6 act:
- 7 (a) Two side marker lamps which display an amber light, 1 on
- 8 each side of the semitrailer, located at 1/2 the distance from
- 9 the front to the rear of the semitrailer.
- (b) Two reflectors which reflect an amber light, 1 on each
- 11 side of the semitrailer, located at 1/2 the distance from the
- 12 front to the rear of the semitrailer.
- (c) Two clearance lamps, 1 on each side of the semitrailer,
- 14 located at 1/2 the distance from the front to the rear and as
- 15 near to the top of the semitrailer as practicable.
- (9) A lamp required under subsection (8) shall be lighted at
- 17 the times specified in section 684 and shall be visible when
- 18 lighted at a distance of 500 feet from the side of the semi-
- 19 trailer on which it is mounted. A reflector required under sub-
- 20 section (8) shall be visible at the times specified in section
- 21 684 from all distances from 50 to 500 feet from the semitrailer
- 22 when directly in front of lawful upper beams of headlamps.
- 23 (10) Notwithstanding any other provisions of this section, a
- 24 person may operate a combination of truck tractor, semitrailer,
- 25 and trailer, or truck tractor and semitrailer or trailer designed
- 26 and used exclusively to transport assembled motor vehicles or
- 27 bodies, recreational vehicles, or boats, which does not exceed a

- 1 total length of 65 feet. Stinger-steered combinations of truck
- 2 tractor and semitrailer shall not exceed a total length of
- 3 75 feet. The load on the combination of vehicles may extend an
- 4 additional 3 feet beyond the front and 4 feet beyond the rear of
- 5 the combination of vehicles. Retractable extensions used to sup-
- 6 port and secure the load that do not extend beyond the allowable
- 7 overhang for the front and rear shall not be included in deter-
- 8 mining the length of a loaded vehicle or combination of
- 9 vehicles. As used in this subsection, "stinger-steered" means a
- 10 semitrailer combination in which the fifth wheel is located on a
- 11 drop frame located behind and below the rearmost axle of the
- 12 power unit.
- 13 (11) A combination of vehicles shall not have more than 11
- 14 axles.
- (12) Notwithstanding any other provisions of this section, a
- 16 number of motor vehicles, wholly or partially assembled, may be
- 17 transported over the highways of this state in combination, uti-
- 18 lizing 1 tow bar or 3 saddle mounts with full mount mechanisms
- 19 and utilizing the motive power of 1 of the vehicles in
- 20 combination. The combination shall not exceed the maximum length
- 21 of 65 feet for the transportation of assembled motor vehicles,
- 22 and the vehicles in the combination shall be adequately and
- 23 securely fastened together in compliance with regulations of the
- 24 state and of any federal agency having jurisdiction over the
- 25 transportation. If motor vehicles are towed by means of triple
- 26 saddle mounts, the towed vehicles shall have brakes acting on all
- 27 wheels which are in contact with the roadway. A combination

- 1 exceeding 55 feet in length may be operated only on highways and
- 2 routes approved and designated for that operation by the state
- 3 transportation department and by local authorities with respect
- 4 to highways under their jurisdiction.
- 5 (13) Notwithstanding any other provisions of this section, a
- 6 person may operate a truck and semitrailer or trailer designed
- 7 and used to transport saw logs, pulpwood, and tree length poles
- 8 that does not exceed an overall length of 70 feet including
- 9 load. These combinations of vehicles shall only be operated upon
- 10 highways designated by the state transportation department or
- 11 local authorities with respect to highways under their
- 12 jurisdiction.
- 13 (14) The total gross weight of a truck tractor, semitrailer,
- 14 and trailer combination or a truck tractor and 2 semitrailers
- 15 combination which exceeds 59 feet in length shall not exceed a
- 16 ratio of 400 pounds per engine net horsepower delivered to clutch
- 17 or its equivalent specified in the SAE handbook published by the
- 18 society of automotive engineers, inc., (1977).
- 19 (15) Except as provided in subsection (2), a person who vio-
- 20 lates this section is responsible for a civil infraction. The
- 21 owner of the vehicle may be charged with a violation of this
- 22 section.