

HOUSE BILL No. 5848

May 18, 1992, Introduced by Rep. Hertel and referred to the Committee on Transportation.

A bill to amend section 722 of Act No. 300 of the Public Acts of 1949, entitled as amended

"Michigan vehicle code,"

as amended by Act No. 346 of the Public Acts of 1988, being section 257.722 of the Michigan Compiled Laws.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

1 Section 1. Section 722 of Act No. 300 of the Public Acts of
2 1949, as amended by Act No. 346 of the Public Acts of 1988, being
3 section 257.722 of the Michigan Compiled Laws, is amended to read
4 as follows:

5 Sec. 722. (1) The maximum axle load shall not exceed the
6 number of pounds designated in the following provisions which
7 prescribe the distance between axles:

1 (a) When the axle spacing is 9 feet or more between axles,
2 the maximum axle load shall not exceed 18,000 pounds for vehicles
3 equipped with high pressure pneumatic or balloon tires.

4 (b) When the axle spacing is less than 9 feet between 2
5 axles but more than 3-1/2 feet, the maximum axle load shall not
6 exceed 13,000 pounds for high pressure pneumatic or balloon
7 tires.

8 (c) When axles are spaced less than 3-1/2 feet apart, the
9 maximum axle load shall not exceed 9,000 pounds per axle.

10 (d) Subdivisions (a), (b), and (c) shall be known as the
11 normal loading maximum.

12 (2) When normal loading is in effect, the state transporta-
13 tion department and local authorities with respect to highways
14 under their jurisdiction may designate certain highways, or sec-
15 tions of those highways, where bridges and road surfaces are ade-
16 quate for heavier loading, which designation may be revised as
17 needed, on which the maximum tandem axle assembly loading shall
18 not exceed 16,000 pounds for any axle of the assembly, if there
19 is no other axle within 9 feet of any axle of the assembly.

20 (3) Except as provided in subsection (8), on a legal combi-
21 nation of vehicles, only 1 tandem axle assembly shall be permit-
22 ted on the designated highways at the gross permissible weight of
23 16,000 pounds per axle, if there is no other axle within 9 feet
24 of any axle of the assembly, and if no other tandem axle assembly
25 in the combination of vehicles exceeds a gross weight of 13,000
26 pounds per axle. When the maximum gross weight of a combination
27 of vehicles with load does not exceed 73,280 pounds, 2 tandem

1 axle assemblies shall be permitted on the designated highways at
2 a gross permissible weight of 16,000 pounds per axle, if there is
3 no other axle within 9 feet of any axle of the assembly.

4 (4) The normal size of tires shall be the rated size as pub-
5 lished by the manufacturers, and the maximum wheel load permissi-
6 ble for any wheel shall not exceed 700 pounds per inch of width
7 of tire.

8 (5) During the months of March, April, and May in each year,
9 the maximum axle load allowable on concrete pavements, or pave-
10 ments with a concrete base, shall be reduced by 25% from the max-
11 imum axle load as specified in this chapter, and the maximum axle
12 loads allowable on all other types of roads during these months
13 shall be reduced by 35% from the maximum axle loads as
14 specified. The maximum wheel load shall not exceed 525 pounds
15 per inch of tire width on concrete and concrete base or 450
16 pounds per inch of tire width on all other roads during the
17 period the seasonal road restrictions are in effect.

18 (6) The state transportation department, or a local author-
19 ity with respect to highways under its jurisdiction, may suspend
20 the restrictions imposed by this section when and where, in its
21 discretion, conditions of the highways or the public health,
22 safety, and welfare so warrant, and may impose the restricted
23 loading requirements of this section on designated highways at
24 any other time that the conditions of the highway may require.

25 (7) For the purpose of enforcement of this act, the gross
26 vehicle weight of a single vehicle and load or a combination of
27 vehicles and loads, shall be determined by weighing individual

17 (a) Twenty thousand pounds on any 1 axle, including all
18 enforcement tolerances.

21 (c) An overall gross weight on a group of 2 or more consecu-
22 tive axles equaling:

25 where W = overall gross weight on a group of 2 or more
26 consecutive axles to the nearest 500 pounds, L = distance in feet

1 between the extreme of a group of 2 or more consecutive axles,
2 and N = number of axles in the group under consideration; except
3 that 2 consecutive sets of tandem axles may carry a gross load of
4 34,000 pounds each if the first and last axles of the consecutive
5 sets of tandem axles are not less than 36 feet apart. The gross
6 vehicle weight shall not exceed 80,000 pounds including all
7 enforcement tolerances. Except for 5 axle truck tractor, semi-
8 trailer combinations having 2 consecutive sets of tandem axles,
9 vehicles having a gross weight in excess of 80,000 pounds or in
10 excess of the vehicle gross weight determined by application of
11 the formula in this subsection shall be subject to the maximum
12 axle loads of subsections (1), (2), and (3). As used in this
13 subsection, "tandem axle weight" means the total weight transmit-
14 ted to the road by 2 or more consecutive axles, the centers of
15 which may be included between parallel transverse vertical planes
16 spaced more than 40 inches, but not more than 96 inches, apart,
17 extending across the full width of the vehicle.

18 (9) NOTWITHSTANDING ANY OTHER PROVISION OF THIS SECTION,
19 EXCEPT FOR SUBSECTION (5), A 20% WEIGHT VARIANCE SHALL BE PERMIT-
20 TED MULTIAXLE VEHICLES OR SINGLE AXLE VEHICLES 17 CUBIC YARDS OR
21 LESS WHEN HAULING SOLID WASTE OR RECYCLABLE MATERIALS TO A SOLID
22 WASTE PROCESSING PLANT, A SOLID WASTE TRANSFER FACILITY, A LAND-
23 FILL, OR A MATERIAL RECOVERY FACILITY ON A STATE OR LOCAL HIGH-
24 WAY, STREET, OR ROADWAY. THIS VARIANCE SHALL APPLY ONLY TO
25 STRAIGHT TRUCK CONFIGURATIONS INCLUDING, BUT NOT LIMITED TO, SIDE
26 LOADERS, FRONT LOADERS, REAR LOADERS, LOAD LUGGERS, RECYCLING

1 TRUCKS, AND ROLL-OFF TRUCKS. THIS VARIANCE DOES NOT APPLY TO THE
2 FOLLOWING:

3 (A) SINGLE AXLE TRUCKS LARGER THAN 17 CUBIC YARDS.

4 (B) SEMITRAILER OR TRAILER COMBINATIONS.