## SENATE BILL NO. 57

January 26, 1999, Introduced by Senators NORTH, KOIVISTO, BENNETT, ROGERS, GOSCHKA and BULLARD and referred to the Committee on Education.

A bill to amend 1990 PA 187, entitled

"The pupil transportation act,"
by amending sections 5, 7, 10, 10a, 17, 19, and 55 (MCL 257.1805, 257.1807, 257.1810, 257.1810a, 257.1817, 257.1819, and 257.1855), section 7 as amended by 1992 PA 227, section 10 as amended by

1996 PA 191, section 10a as added by 1990 PA 322, and section 55

as amended by 1991 PA 184.

## THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

- 1 Sec. 5. (1) "Modified school bus" means a school bus of any
- 2 age with a factory installed fuel system which THAT has been
- 3 modified to operate on a fuel source other than gasoline or
- 4 diesel fuel.
- 5 (2) "MOTOR BUS" AND "MOTOR CARRIER OF PASSENGERS" MEAN THOSE
- 6 TERMS AS DEFINED IN SECTION 3 OF THE MOTOR BUS TRANSPORTATION
- 7 ACT, 1982 PA 432, MCL 474.103.

00554'99 TJS

- 1 (3) <del>(2)</del> "Nonpublic school" means a private school, a
- 2 denominational school, or a parochial school as defined by law.
- 3 (4) -(3) "Public school" means a local school district, a
- 4 local act school district, A PUBLIC SCHOOL ACADEMY, A UNIVERSITY
- 5 SCHOOL, or an intermediate school district as defined by law.
- (5) (4) "Pupil transportation vehicle" means any vehicle
- 7 other than a school bus WITH A MANUFACTURER'S RATED SEATING
- 8 CAPACITY OF 11 OR MORE PASSENGERS, INCLUDING THE DRIVER, THAT IS
- 9 used to transport pupils to or from school or school-related
- 10 events. Pupil transportation vehicle does not include a vehicle
- 11 operated by a municipally owned transportation system or by a
- 12 carrier certified by the state transportation department MOTOR
- 13 CARRIER OF PASSENGERS OR A PUBLIC TRANSIT AGENCY, OR A VEHICLE
- 14 USED BY A PARENT OR A PARENT'S DESIGNEE TO TRANSPORT HIS OR HER
- 15 CHILDREN TO OR FROM SCHOOL OR SCHOOL-RELATED EVENTS.
- 16 (6) <del>(5)</del> "Rehabilitated school bus" means a bus <del>which</del>
- 17 THAT is at least 4 years old and has accumulated at least 100,000
- 18 miles, or is 7 years old; and which THAT has been thoroughly
- 19 inspected and had all systems repaired, replaced, or adjusted to
- 20 meet the department of state police inspection requirements
- 21 including but not limited to:
- 22 (a) Engine overhaul of short block.
- 23 (b) New tires on the front axle.
- 24 (c) New recap tires on the rear axle.
- 25 (d) New brake linings and drums.
- (e) New hydraulic brake lines.

- 1 (f) New front and rear springs.
- 2 (g) New paint in the interior.
- 3 (h) New exhaust system.
- 4 (7)  $\overline{(6)}$  "Rule" means a rule promulgated pursuant to the
- 5 administrative procedures act of 1969, Act No. 306 of the Public
- 6 Acts of 1969, being sections 24.201 to 24.328 of the Michigan
- 7 Compiled Laws 1969 PA 306, MCL 24.201 TO 24.328.
- 8 (8)  $\overline{(7)}$  "School" means either a public school or a nonpub-
- 9 lic school, or both.
- 10 Sec. 7. (1) "School bus" means a motor vehicle, other than
- 11 a station wagon or passenger van PUPIL TRANSPORTATION VEHICLE,
- 12 with a manufacturer's rated seating capacity of  $\frac{16}{1}$  11 or more
- 13 passengers, INCLUDING THE DRIVER, used for the transportation of
- 14 school pupils to and OR from school and OR school-related
- 15 events which either THAT is owned by a school or -, if owned by
- 16 an entity other than a school, is transporting school IS USED TO
- 17 TRANSPORT pupils under a contract or agreement with a school.
- 18 School bus does not include a vehicle operated by a public tran-
- 19 sit agency or authority or by a MOTOR carrier certified by the
- 20 state transportation department unless the vehicle is used exclu-
- 21 sively to transport -school pupils or is used to transport
- 22 -school pupils along a route designed to serve 1 or more schools
- 23 in a school district if elementary school pupils along the route
- 24 are required to cross the highway or roadway, as described in
- 25 section 55. For the purposes of this act, a parent, parent's
- 26 designee, or guardian transporting their HIS OR HER child or
- 27 another child with written permission of the other child's parent

- 1 or guardian on a school-related event, if not compensated by the
- 2 school, shall not be considered an agent of the school.
- 3 (2) "SCHOOL TRANSPORTATION VEHICLE" MEANS ANY MOTOR VEHICLE
- 4 WITH A MANUFACTURER'S RATED SEATING CAPACITY OF 10 PASSENGERS OR
- 5 LESS, INCLUDING THE DRIVER, WHEN OPERATED FOR THE SCHEDULED
- 6 TRANSPORTATION OF PUPILS TO OR FROM SCHOOL OR SCHOOL-RELATED
- 7 EVENTS. SCHOOL TRANSPORTATION VEHICLE DOES NOT INCLUDE A VEHICLE
- 8 USED BY A PARENT OR PARENT'S DESIGNEE TO TRANSPORT CHILDREN TO OR
- 9 FROM SCHOOL OR SCHOOL-RELATED EVENTS.
- 10 (3)  $\overline{(2)}$  "Type I school bus" means a school bus with a
- 11 gross vehicle weight rating of more than 10,000 pounds.
- 12 (4)  $\overline{(3)}$  "Type II school bus" means a school bus with a
- 13 gross vehicle rating of 10,000 pounds or less.
- 14 (5)  $\overline{(4)}$  "Type I premium school bus" means a school bus
- 15 with a passenger capacity of over 66 pupils and any other school
- 16 bus purchased by a district at a cost for the vehicle, excluding
- 17 interest and special equipment, which exceeds by more than 15%
- 18 the average cost of a school bus meeting state minimum specifica-
- 19 tions of the same capacity purchased during the same year.
- Sec. 10. (1) Each motor vehicle owned OR OPERATED by a
- 21 public -, OR private -, or governmental agency and operated
- 22 NONPUBLIC SCHOOL, AN AGENT OF A SCHOOL, A PRIVATE BUSINESS, OR A
- 23 UNIT OF GOVERNMENT for the transportation of passengers PUPILS
- 24 to or from school and OR school-related events shall meet or
- 25 exceed the <del>passenger protection</del> federal motor vehicle safety
- 26 standards applicable to the construction and sale of that vehicle
- 27 AND FOR ALL SEATING POSITIONS IN THAT VEHICLE. A vehicle for

- 1 which there are no applicable passenger protection federal motor
- 2 vehicle safety standards shall not be used to transport passen-
- 3 gers to and from school and school related events. A SCHOOL OR
- 4 AN AGENT OF A SCHOOL MAY TRANSPORT PUPILS WITH DISABILITIES IN
- 5 MOBILE SEATING DEVICES IN ACCORDANCE WITH FEDERAL STANDARDS SPE-
- 6 CIFICALLY APPLICABLE TO SUCH PUPILS, THEIR WHEELCHAIRS, AND
- 7 RELATED WHEELCHAIR SECUREMENT AND OCCUPANT PROTECTION SYSTEMS.
- 8 (2) Vehicles, other than school buses, shall meet the
- 9 requirements of this section by October 1, 2002 A VEHICLE, OTHER
- 10 THAN A SCHOOL BUS, WITH A MANUFACTURER'S RATED SEATING CAPACITY
- 11 OF 11 OR MORE PASSENGERS, INCLUDING THE DRIVER, SHALL NOT BE USED
- 12 TO TRANSPORT PUPILS TO OR FROM SCHOOL OR SCHOOL-RELATED EVENTS
- 13 AFTER OCTOBER 1, 2002, EXCEPT AS PROVIDED IN THIS ACT.
- 14 (3) A school shall not purchase a vehicle to be used to
- 15 transport -passengers PUPILS to -and OR from school -and OR
- 16 school-related events HAVING A MANUFACTURER'S RATED SEATING
- 17 CAPACITY OF 11 OR MORE PASSENGERS, INCLUDING THE DRIVER, that
- 18 does not meet or exceed the passenger protection federal motor
- 19 vehicle safety standards applicable to that vehicle. A school
- 20 shall not purchase a vehicle to be used to transport passengers
- 21 to -and OR from school -and OR school-related events for which
- 22 there are no applicable passenger protection federal motor vehi-
- 23 cle safety standards. This subsection <del>shall apply</del> APPLIES to
- 24 vehicles, other than school buses, purchased on or after
- 25 October 1, 1993.
- 26 (4) Vehicles used by parents or a parent's designee to
- 27 transport their children to and from school and school related

- 1 events under contract with the school are exempt from the
- 2 requirements of this section. SUBSECTION (2) DOES NOT APPLY TO A
- 3 COMMERCIAL MOTOR VEHICLE OPERATED BY A CARRIER CERTIFICATED BY
- 4 THE STATE TRANSPORTATION DEPARTMENT, OR A BUS OPERATED BY A
- 5 PUBLIC TRANSIT AGENCY OR AUTHORITY EXCLUDED FROM THE DEFINITION
- 6 OF SCHOOL BUS AS DESCRIBED IN SECTION 7(1).
- 7 Sec. 10a. (1) A school district may use a vehicle con-
- 8 structed to standards comparable to those used by Greyhound-type
- 9 <del>buses Contract with a motor carrier of passengers for a motor</del>
- 10 BUS TO BE USED for occasional transportation OF PUPILS to OR FROM
- 11 school-related events. -, provided that a contract for the con-
- 12 struction and delivery of that vehicle was entered into after
- 13 January 1, 1990, but before the effective date of this act. This
- 14 vehicle shall not be used for the regular route transportation of
- 15 students to and from school and home.
- 16 (2) THE DEPARTMENT OF EDUCATION MAY AUTHORIZE THE USE OF A
- 17 MOTOR BUS FOR THE REGULAR ROUTE TRANSPORTATION OF PUPILS TO OR
- 18 FROM SCHOOL OR HOME. THE AUTHORIZATION SHALL BE IN WRITING AND
- 19 SHALL INCLUDE CONDITIONS OR RESTRICTIONS THAT ARE NECESSARY TO
- 20 SAFEGUARD THE HEALTH, SAFETY, AND WELFARE OF THE PUPILS.
- 21 Sec. 17. (1) THIS SECTION APPLIES TO SCHOOL BUSES MANUFAC-
- 22 TURED BEFORE OCTOBER 1, 1990 THAT HAVE NOT BEEN RETROFITTED TO
- 23 MEET THE REQUIREMENTS OF SECTION 19.
- 24 (2)  $\overline{(1)}$  A school bus shall be equipped with signal  $\overline{}$
- 25 LIGHTS mounted as high and widely spaced laterally as practicable
- 26 which shall be THAT ARE capable of displaying to the front 2
- 27 OVERHEAD alternately flashing red lights located at the same

- 1 level and to the rear 2 OVERHEAD alternately flashing red lights
- 2 located at the same level. These sealed beam lights shall have
- 3 sufficient intensity to be visible from a distance of not less
- 4 than 500 feet in normal sunlight.
- 5 (3) (2) Alternately OVERHEAD ALTERNATELY flashing stop
- 6 lights STOPLIGHTS shall be operated by a manually operated
- 7 switch and detached from any other instrument on the bus. A
- 8 flashing light shall not be connected to the brakes or the serv-
- 9 ice door on school buses manufactured before October 1, 1990. A
- 10 3-inch black area shall be provided around sealed beam flasher
- 11 lamps front and rear. Lamps indicating alternating flashing
- 12 light operation shall be visible to the driver when in a normal
- 13 seated position.
- 14 (3) This section shall apply to school buses manufactured
- 15 before October 1, 1990 that have not been retrofitted to meet the
- 16 requirements of section 19.
- 17 Sec. 19. (1) THIS SECTION APPLIES TO NEW SCHOOL BUSES MANU-
- 18 FACTURED ON OR AFTER OCTOBER 1, 1990 AND TO SCHOOL BUSES MANUFAC-
- 19 TURED BEFORE OCTOBER 1, 1990 THAT ARE RETROFITTED TO MEET THE
- 20 REQUIREMENTS OF THIS SECTION.
- 21 (2) -(1) A school bus shall be equipped with signal -lamps
- 22 LIGHTS mounted as high and widely spaced laterally as practicable
- 23 which shall be THAT ARE capable of displaying to the front 2
- 24 OVERHEAD alternately flashing red lamps LIGHTS located at the
- 25 same level and to the rear 2 OVERHEAD alternately flashing red
- 26 <del>lamps</del> LIGHTS located at the same level.

- (3)  $\frac{(2)}{(2)}$  In addition to the 4 red  $\frac{1}{(2)}$  LIGHTS described 1 2 in subsection -(1) (2), 4 amber -lamps LIGHTS shall be 3 installed near each red signal -lamp LIGHT, at the same level, 4 but closer to the vertical center line of the bus. The system of 5 red and amber signal -lamps LIGHTS shall be wired so that the **6** amber <del>lamps</del> LIGHTS are energized manually, and the red <del>lamps</del> 7 LIGHTS are automatically energized, with the amber -lamps LIGHTS 8 being automatically de-energized, when the bus service door is 9 opened. 10 (4)  $\overline{(3)}$  The area around the lens of each OVERHEAD alter-11 nately flashing signal -lamp LIGHT and extending outward approx-12 imately 3 inches shall be painted black. In installations where 13 there is no flat vertical portion of body immediately surrounding 14 the entire lens of a -lamp LIGHT, a circular or square band of 15 black approximately 3 inches wide, immediately below and to both 16 sides of a lens, shall be painted on the body or roof area 17 against which the signal -lamp LIGHT is seen from a distance of 18 500 feet along the axis of the vehicle. Visors or hoods with an 19 appropriate black background to fit their shape and roofcap may 20 also be used. These amber and red sealed beam lights shall have 21 sufficient intensity to be visible from a distance of not less 22 than 500 feet in normal sunlight. - Lamps LIGHTS indicating 23 alternately flashing light operation shall be visible to the
- 25 (4) This section shall apply to new school buses manufac-
- 26 tured on or after October 1, 1990 and to school buses

24 driver when in a normal seated position.

- 1 manufactured before October 1, 1990 that are retrofitted to meet
- 2 the requirements of this section.
- 3 Sec. 55. (1) A school bus driver shall actuate alternately
- 4 flashing lights only when the school bus is stopped or stopping
- 5 on a highway or private road for the purpose of receiving or dis-
- 6 charging pupils in the manner provided in this act. A school bus
- 7 driver shall not actuate the alternately flashing lights when
- 8 operating on a public highway or private road and transporting
- 9 passengers primarily other than school pupils.
- 10 (2) The driver of a school bus while operating upon the
- 11 public highways or private roadways open to the public shall
- 12 receive or discharge pupils from the bus in the following
- 13 manner:
- 14 (a) If pupils are required to cross the roadway, the driver
- 15 of a school bus equipped with only the alternately flashing
- 16 OVERHEAD red lights in accordance with section 17 shall activate
- 17 the ALTERNATELY flashing OVERHEAD red lights not less than 200
- 18 feet before the stop, and park STOP the school bus as far off
- 19 TO the right side of the roadway HIGHWAY or private road as
- 20 possible TO PROVIDE for the safety of the pupils being boarded or
- 21 discharged, and continue to activate the alternately flashing
- 22 OVERHEAD red lights while receiving or discharging pupils.
- 23 Before resuming motion, the driver shall deactivate these lights
- 24 and allow congested traffic to disperse where practicable. The
- 25 deactivation of these lights is the signal for stopped traffic to
- 26 proceed.

(b) If the pupils are required to cross the roadway, the 1 2 driver of a school bus equipped with red and amber alternately 3 flashing OVERHEAD lights in accordance with section 19 shall 4 activate the alternately flashing OVERHEAD amber lights not less 5 than 200 feet before the stop, park STOP the bus as far off 6 TO the right side of the roadway HIGHWAY or private road as is 7 possible TO PROVIDE for the safety of the pupils being boarded or 8 discharged, deactivate the -amber ALTERNATELY flashing OVERHEAD 9 AMBER lights, and activate the alternately flashing OVERHEAD red 10 lights while receiving or discharging pupils. Before resuming 11 motion, the driver shall deactivate these lights and allow con-12 gested traffic to disperse where practicable. The deactivation 13 of these lights is the signal for stopped traffic to proceed. (c) If the pupils are not required to cross the roadway and 15 where the road has adequate width for the school bus to be pulled 16 to the far right of the -roadway HIGHWAY or private road allow-17 ing traffic to flow and to provide for the safety of pupils being 18 boarded or discharged, the driver may activate the hazard warning 19 lights not less than 200 feet before the stop and continue to 20 display the lights until the process of receiving or discharging 21 passengers has been completed if the posted LAWFUL speed limit 22 is 35 miles per hour or less. Before resuming motion, the driver 23 shall deactivate these lights. The driver of a school bus shall 24 only use this procedure at stops where the school administrator 25 or board approved contractor PERSON OR ENTITY UNDER CONTRACT 26 WITH A SCHOOL TO PROVIDE PUPIL TRANSPORTATION SERVICES has 27 approved its use. If this hazard warning light option is not

- 1 used, the driver shall use the appropriate procedure in
- 2 subdivision (a) or (b) as if pupils were required to cross the
- 3 roadway HIGHWAY.
- 4 (d) Except as provided in subdivision (c), if the pupils are
- 5 not required to cross the <del>roadway</del> HIGHWAY and where the bus may
- 6 be pulled off the -roadway HIGHWAY or private road or where the
- 7 road has adequate width for the school bus to be pulled off to
- 8 the far right of the roadway HIGHWAY or private road leaving
- 9 the normal traffic flow unobstructed and to provide for the
- 10 safety of pupils being boarded or discharged, the driver may
- 11 activate the hazard warning lights not less than 200 feet before
- 12 the stop and continue to display the lights until the process of
- 13 receiving or discharging passengers has been completed. Before
- 14 resuming motion, the driver shall deactivate these lights. The
- 15 driver of a school bus shall only use this procedure at stops
- 16 where the school administrator or board approved contractor
- 17 ENTITY UNDER CONTRACT WITH A SCHOOL TO PROVIDE PUPIL TRANSPORTA-
- 18 TION SERVICES has approved its use. If this hazard warning light
- 19 option is not used, the driver shall use the appropriate proce-
- 20 dure in subdivision (a) or (b) as if pupils were required to
- **21** cross the <del>roadway</del> HIGHWAY.
- (e) The distance of not less than 200 feet required for
- 23 light activation by this subsection shall be measured on the
- 24 roadway HIGHWAY or private road on which the stop is made for
- 25 receiving or discharging pupils.
- 26 (3) Passengers PUPILS crossing the road upon being
- 27 discharged from a school bus shall cross in front of the stopped

- 1 school bus. If a school district authorizes its school bus
- 2 drivers to signal pupils to cross in front of the stopped school
- 3 bus, the signal shall be uniform throughout the school district.
- 4 (4) The driver of a school bus shall not stop the bus for
- 5 the purpose of receiving or discharging pupils in the following
- 6 instances:
- 7 (a) Within 200 feet of a public highway or roadway intersec-
- 8 tion unless the stop is approved by the school administrator or
- 9 board approved contractor ENTITY UNDER CONTRACT WITH A SCHOOL
- 10 TO PROVIDE PUPIL TRANSPORTATION SERVICES.
- 11 (b) Upon a limited access highway or freeway, or upon any
- 12 other highway or roadway that has been divided into 2 roadways by
- 13 leaving an intervening space, a physical barrier, or clearly
- 14 divided sections so constructed as to impede vehicular traffic if
- 15 the pupils are required to cross the highway or roadway.
- 16 (c) Upon a highway or roadway constructed or <del>designed</del>
- 17 MARKED to permit 3 or more separate lanes of vehicular traffic in
- 18 either direction if the pupils are required to cross the highway
- 19 or roadway.
- 20 (5) The driver of a school bus when using the alternately
- 21 flashing OVERHEAD red -stopping lights shall not stop the bus ON
- 22 ANY HIGHWAY OR ROADWAY for the purpose of receiving or discharg-
- 23 ing pupils -in UNDER the following -instances CONDITIONS:
- 24 (a) Unless IF THE LAWFUL SPEED LIMIT IS MORE THAN 35 MILES
- 25 PER HOUR AND the STOPPED bus is NOT clearly and continuously vis-
- 26 ible in its stopped position to approaching vehicles on that
- 27 highway or roadway for -not less than AT LEAST 400 feet. WHEN

- 1 THE DISTANCE FROM THE STOPPED BUS TO THE END OF THE HIGHWAY OR
- 2 ROADWAY IS LESS THAN 400 FEET, CLEAR AND CONTINUOUS VISIBILITY
- 3 MUST BE AVAILABLE FROM THE BUS TO THE END OF THE HIGHWAY OR
- 4 ROADWAY.
- 5 (B) IF THE LAWFUL SPEED LIMIT IS 35 MILES PER HOUR OR LESS
- 6 AND THE STOPPED BUS IS NOT CLEARLY AND CONTINUOUSLY VISIBLE TO
- 7 APPROACHING VEHICLES ON THAT HIGHWAY OR ROADWAY, FOR AT LEAST 200
- 8 FEET. WHEN THE DISTANCE FROM THE STOPPED BUS TO THE END OF THE
- 9 HIGHWAY OR ROADWAY IS LESS THAN 200 FEET, CLEAR AND CONTINUOUS
- 10 VISIBILITY MUST BE AVAILABLE FROM THE BUS TO THE END OF THE HIGH-
- 11 WAY OR ROADWAY.
- 12 (C)  $\frac{\text{(b)}}{\text{(b)}}$  Within 50 feet of an intersection if the intersec-
- 13 tion is controlled by a traffic stop and go signal.
- 14 (6) A school may provide instruction on proper school bus
- 15 etiquette which may include, but not be limited to, boarding and
- 16 leaving the bus, evacuation of the bus in an emergency, and road
- 17 crossing procedures and the correct hand signal in the district,
- 18 if any. If a school uses school bus drivers for this instruc-
- 19 tion, the state board may reimburse the school for this
- 20 training.
- 21 (7) For the purpose of this section, "required to cross the
- 22 highway or roadway" does not include crossing the -road HIGHWAY
- 23 OR ROADWAY with the assistance of a traffic control signal, or
- 24 with the assistance of a SCHOOL crossing guard as defined in
- 25 section 57b of the Michigan vehicle code, Act No. 300 of the
- 26 Public Acts of 1949, being section 257.57b of the Michigan

14

- 1 Compiled Laws 1949 PA 300, MCL 257.57B, and applies only to the
- 2 -road HIGHWAY OR ROADWAY on which the stop is being made.

00554'99 Final page.