

HOUSE BILL No. 4512

April 9, 2013, Introduced by Rep. Geiss and referred to the Committee on Regulatory Reform.

A bill to amend 1941 PA 207, entitled
"Fire prevention code,"
by amending section 5c (MCL 29.5c), as amended by 2006 PA 189.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

1 Sec. 5c. (1) A person shall not establish or maintain 1 or
2 more of the following without obtaining a certificate from the
3 department of environmental quality:

4 (a) A flammable compressed gas or liquefied petroleum gas
5 container filling location.

6 (b) An aboveground flammable compressed gas or liquefied
7 petroleum gas storage location that has a tank with a water
8 capacity of more than 2,000 gallons or has 2 or more tanks with an
9 aggregate water capacity of more than 4,000 gallons.

10 (c) An aboveground storage location for a flammable liquid or

1 combustible liquid that has an individual tank storage capacity of
2 more than 1,100 gallons. Crude petroleum collection tanks that
3 receive crude petroleum directly from a wellhead and are certified
4 by the department of environmental quality may be maintained
5 without further inspection by the department of environmental
6 quality, except as the department of environmental quality
7 considers necessary to ~~assure~~**ENSURE** compliance with this act.

8 (2) The department of environmental quality may require that a
9 person obtain approval from the department of environmental quality
10 before the installation of an aboveground storage tank for
11 flammable or combustible liquids that has an individual tank
12 storage capacity of 1,100 gallons or less. However, this
13 requirement does not apply to farm location storage tanks of 1,100
14 gallons or less capacity used for storing motor fuel for
15 noncommercial purposes or heating oil for consumptive use on the
16 premises where stored.

17 (3) IF AN ABOVEGROUND STORAGE TANK DESIGNED FOR FLAMMABLE OR
18 COMBUSTIBLE LIQUIDS WITH A CAPACITY OF 10,000 GALLONS OR MORE HAS
19 NOT BEEN IN USE FOR 5 OR MORE YEARS, THE OWNER OR OPERATOR SHALL
20 DISASSEMBLE THE TANK AND PROPERLY DISPOSE OF THE PARTS.