

HOUSE BILL No. 4956

September 14, 2017, Introduced by Reps. Cole, Liberati, Webber, Leutheuser and Chirkun
and referred to the Committee on Transportation and Infrastructure.

A bill to amend 1949 PA 300, entitled
"Michigan vehicle code,"
by amending section 719 (MCL 257.719), as amended by 2017 PA 35.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

1 Sec. 719. (1) A vehicle unloaded or with load shall not exceed
2 a height of 13 feet 6 inches. The owner of a vehicle that collides
3 with a lawfully established bridge or viaduct is liable for all
4 damage and injury resulting from a collision caused by the height
5 of the vehicle, whether the clearance of the bridge or viaduct is
6 posted or not.

7 (2) Lengths described in this subsection shall be known as the
8 normal length maximum. Except as provided in subsection (3), the
9 following vehicles and combinations of vehicles shall not be

1 operated on a highway in this state in excess of these lengths:

2 (a) Subject to subsection (9), any single vehicle: 40 feet; a
3 crib vehicle on which logs are loaded lengthwise of the vehicle:
4 42.5 feet; any single bus or motor home: 45 feet.

5 (b) Articulated buses: 65 feet.

6 (c) Notwithstanding any other provision of this section, a
7 combination of a truck and semitrailer or trailer, or a truck
8 tractor, semitrailer, and trailer, or truck tractor and semitrailer
9 or trailer, designed and used exclusively to transport assembled
10 motor vehicles or bodies, recreational vehicles, or boats: 65 feet.
11 A combination of a truck and semitrailer or trailer, or a truck
12 tractor, semitrailer, and trailer, or a truck tractor and
13 semitrailer or trailer designed and used to transport boats from
14 the manufacturer, or a stinger-steered combination: 75 feet. The
15 load on the combinations of vehicles described in this subdivision
16 may extend an additional 3 feet beyond the front and 4 feet beyond
17 the rear of the combinations of vehicles. Retractable extensions
18 used to support and secure the load that do not extend beyond the
19 allowable overhang for the front and rear shall not be included in
20 determining length of a loaded vehicle or vehicle combination.

21 (d) Truck tractor and semitrailer combinations: no overall
22 length, the semitrailer: 50 feet.

23 (e) Except as provided in subdivision (j), truck and
24 semitrailer or trailer: 59 feet.

25 (f) Except as provided in subdivision (g), truck tractor,
26 semitrailer, and trailer, or truck tractor and 2 semitrailers: 59
27 feet.

1 (g) A truck tractor, semitrailer, and trailer, or a truck
2 tractor and 2 semitrailers, in which no semitrailer or trailer is
3 more than 28-1/2 feet long: 65 feet. This subdivision only applies
4 while the vehicle is being used for a business purpose reasonably
5 related to picking up or delivering a load and only if each
6 semitrailer or trailer is equipped with a device or system capable
7 of mechanically dumping construction materials or dumping
8 construction materials by force of gravity.

9 (h) More than 1 motor vehicle, wholly or partially assembled,
10 in combination, utilizing 1 tow bar or 3 saddle mounts with full
11 mount mechanisms and utilizing the motive power of 1 of the
12 vehicles in combination: 55 feet.

13 (i) A recreational vehicle that has its own motive power, in
14 combination with a trailer: 65 feet or, if the operator of the
15 recreational vehicle has a group commercial motor vehicle
16 designation on his or her operator's or chauffeur's license, 75
17 feet.

18 (j) Truck and trailer combinations designed and used to
19 transport agricultural drainage tubing: 75 feet.

20 (3) Notwithstanding subsection (2), the following vehicles and
21 combinations of vehicles shall not be operated on a designated
22 highway of this state in excess of these lengths:

23 (a) Truck tractor and semitrailer combinations: no overall
24 length limit, the semitrailer 53 feet. ~~All semitrailers longer than~~
25 ~~50 feet shall have a wheelbase of 37.5 to 40.5 feet plus or minus~~
26 ~~0.5 feet, measured from the kingpin coupling to the center of the~~
27 ~~rear axle or the center of the rear axle assembly. City, village,~~

1 or county authorities may prohibit stops of vehicles with a
2 semitrailer longer than 50 feet within their jurisdiction unless
3 the stop occurs along appropriately designated routes, or is
4 necessary for emergency purposes or to reach shippers, receivers,
5 warehouses, and terminals along designated routes.

6 (b) Truck and semitrailer or trailer combinations: 65 feet,
7 except that a person may operate a truck and semitrailer or trailer
8 designed and used to transport saw logs, pulpwood, and tree length
9 poles that does not exceed an overall length of 70 feet or a crib
10 vehicle and semitrailer or trailer designed and used to transport
11 saw logs that does not exceed an overall length of 75 feet. A crib
12 vehicle and semitrailer or trailer designed to and used to
13 transport saw logs shall not exceed a gross vehicle weight of
14 164,000 pounds. A person may operate a truck tractor and
15 semitrailer designed and used to transport saw logs, pulpwood, and
16 tree length wooden poles with a load overhang to the rear of the
17 semitrailer which does not exceed 6 feet if the semitrailer does
18 not exceed 50 feet in length.

19 (c) Notwithstanding subsection (5)(d), a truck tractor with a
20 log slasher unit and a log saw unit: no overall limit if the length
21 of each unit does not exceed 28-1/2 feet, or the overall length of
22 the log slasher unit and the log saw unit, as measured from the
23 front of the first towed unit to the rear of the second towed unit
24 while the units are coupled together, does not exceed 58 feet. The
25 coupling devices of the truck tractor and units set forth in this
26 subdivision shall meet the requirements established under the motor
27 carrier safety act of 1963, 1963 PA 181, MCL 480.11 to 480.25.

1 (d) Truck tractor and 2 semitrailers, or truck tractor,
2 semitrailer, and trailer combinations: no overall length limit, if
3 the length of each semitrailer or trailer does not exceed 28-1/2
4 feet each, or the overall length of the semitrailer and trailer, or
5 2 semitrailers as measured from the front of the first towed unit
6 to the rear of the second towed unit while the units are coupled
7 together does not exceed 58 feet.

8 (e) More than 1 motor vehicle, wholly or partially assembled,
9 in combination, utilizing 1 tow bar or 3 saddle mounts with full
10 mount mechanisms and utilizing the motive power of 1 of the
11 vehicles in combination: 97 feet.

12 (f) Truck tractor and lowboy semitrailer combinations: no
13 maximum overall length, if the lowboy semitrailer does not exceed
14 59 feet, except as otherwise permitted under this subdivision. A
15 ~~lowboy semitrailer wheelbase shall not exceed 55 feet as measured~~
16 ~~from the kingpin coupling to the center of the rear axle.~~ A lowboy
17 semitrailer more than 59 feet in length shall not operate with more
18 than any combination of 4 axles on the lowboy unless an oversized
19 load permit is issued by the state transportation department or a
20 local authority with respect to highways under its jurisdiction. As
21 used in this subdivision, "lowboy semitrailer" means a flatbed
22 semitrailer with a depressed section that has the specific purpose
23 of being lowered and raised for loading and unloading.

24 (4) Notwithstanding any other provision of this section, a
25 combination of a truck and semitrailer, or truck tractor and
26 semitrailer, used exclusively to transport assembled motor vehicles
27 or bodies that have a trailer length of 53 feet may have a load

1 that extends an additional 3 feet beyond the front of the trailer
2 and 4 feet beyond the rear of the trailer. Retractable extensions
3 used to support and secure the load that do not extend beyond the
4 allowable overhang for the front and rear shall not be included in
5 determining length of a loaded vehicle or vehicle combination. The
6 total overall length loaded of the combination of vehicles
7 described in this subsection shall not exceed 79 feet.

8 (5) The following combinations and movements are prohibited:

9 (a) A truck shall not haul more than 1 trailer or semitrailer,
10 and a truck tractor shall not haul more than 2 semitrailers or 1
11 semitrailer and 1 trailer in combination at any 1 time, except that
12 a farm tractor may haul 2 wagons or trailers, or garbage and refuse
13 haulers may, during daylight hours, haul up to 4 trailers for
14 garbage and refuse collection purposes, not exceeding in any
15 combination a total length of 55 feet and at a speed limit not to
16 exceed 15 miles per hour.

17 (b) A combination of vehicles or a vehicle shall not have more
18 than 11 axles, except when operating under a valid permit issued by
19 the state transportation department or a local authority with
20 respect to a highway under its jurisdiction.

21 (c) Any combination of vehicles not specifically authorized
22 under this section is prohibited.

23 (d) Except as provided in subsection (3)(c), a combination of
24 2 semitrailers pulled by a truck tractor, unless each semitrailer
25 uses a fifth wheel connecting assembly that conforms to the
26 requirements of the motor carrier safety act of 1963, 1963 PA 181,
27 MCL 480.11 to 480.25.

1 (e) A vehicle or a combination of vehicles shall not carry a
2 load extending more than 3 feet beyond the front of the lead
3 vehicle.

4 (f) A vehicle described in subsections (2)(e) and (3)(e)
5 employing triple saddle mounts unless all wheels that are in
6 contact with the roadway have operating brakes.

7 (6) All combinations of vehicles under this section shall
8 employ connecting assemblies and lighting devices that are in
9 compliance with the motor carrier safety act of 1963, 1963 PA 181,
10 MCL 480.11 to 480.25.

11 (7) The total gross weight of a truck tractor, semitrailer,
12 and trailer combination or a truck tractor and 2 semitrailers
13 combination that exceeds 59 feet in length shall not exceed a ratio
14 of 400 pounds per engine net horsepower delivered to clutch or its
15 equivalent specified in the handbook published by the Society of
16 Automotive Engineers, Inc. (SAE), 1977 edition.

17 (8) A person who violates this section is responsible for a
18 civil infraction. The owner of the vehicle may be charged with a
19 violation of this section.

20 (9) The provisions in subsections (2)(a) and (3)(b)
21 prescribing the length of a crib vehicle on which logs are loaded
22 lengthwise do not apply unless 23 USC 127(d) is amended to allow
23 crib vehicles carrying logs to be loaded as described in this
24 section.

25 (10) As used in this section:

26 (a) "Designated highway" means a highway approved by the state
27 transportation department or a local authority with respect to a

1 highway under its jurisdiction.

2 (b) "Length" means the total length of a vehicle, or
3 combination of vehicles, including any load the vehicle is
4 carrying. Length does not include devices described in 23 CFR
5 658.16 and 23 CFR part 658, appendix D, 23 CFR 658.16 and 23 CFR
6 part 658, appendix D, as on file with the secretary of state are
7 adopted by reference. A safety or energy conservation device shall
8 be excluded from a determination of length only if it is not
9 designed or used for the carrying of cargo, freight, or equipment.
10 Semitrailers and trailers shall be measured from the front vertical
11 plane of the foremost transverse load supporting structure to the
12 rearmost transverse load supporting structure. Vehicle components
13 not excluded by law shall be included in the measurement of the
14 length, height, and width of the vehicle.

15 (c) "Stinger-steered combinations" means a truck tractor and
16 semitrailer combination in which the fifth wheel is located on a
17 drop frame located behind and below the rearmost axle of the power
18 unit.

19 Enacting section 1. This amendatory act takes effect 90 days
20 after the date it is enacted into law.